


Suction Hose

The PVC Plasticised hose has an incorporated spiral reinforcement of anti-shock rigid PVC. The inside surface is smooth and the outside is a light corrugate surface. The hose measures 50mm x 2.4 metres. Comes coupled with female Aluminium camlock and 50mm MBSP steel galvanised.



SKU:023900

FEATURES:

- Very Strong
- Resistant to crushing
- Resistant to abrasion, atmospherical agents and most chemicals
- Temperature rated $-10^{\circ}\text{C} + 60^{\circ}\text{C}$

Foot Valve

The Firemaster foot valve is manufactured in a heavy duty PVC. This unit is a combination foot valve and strainer for use with suction hose coupled with 50mm MBSP. The spring loaded valve ensures instantaneous closing. Dismantles easily for cleaning and maintenance.



SKU:8000

Suction Strainers

- 75mm round thread (SKU:053000)
- 100mm round thread (SKU:053100)
- 100mm round thread low level (SKU:053200)
- 140mm round thread (SKU:053300)



SKU:053000

Basket Strainer & Skirt

- 75 mm (SKU:7208)
- 100 mm (SKU:7209)
- 140 mm (SKU:7211)
- 50 mm (for Wajax Forestry Pump) (SKU:7213)



SKU:7213

www.pslfireandsafety.co.nz

PO Box 69-028 Glendene,
Auckland 0645, NZ
+64 9 818 8048

