



SPECIFICATIONS

Interior dimensions	L18.0" x W13.0" x H9.5" L457mm x W330mm x H241mm
Exterior dimensions	L19.9" x W16.1" x H10.1" L505mm x W409mm x H257mm
Weight (empty)	8.0 lbs 3.6 kg
Lid depth	2.1" 53mm
Base depth	7.4" 188mm
Max buoyancy	65 lbs 29.5 kg
Temperature range	Min -20°F (-29°C) Max 140°F (60°C)
Airline cabin carry-on	No
Watertight	Yes - IP67
Warranty	Conditional lifetime guarantee

CERTIFICATIONS

	IPX7 INGRESS PROTECTION - WATERPROOF
	IP6X INGRESS PROTECTION - DUSTPROOF
	ATA SPECIFICATION 300 - CATEGORY 1 IMPACT
	ASTM D-4169 DC-18 - DROP TEST
	ASTM D-4169 DC-18 - VIBRATION
	ASTM D-4169 DC-18 - RAINFALL
	MIL-STD-810F - IMMERSION

MATERIALS

Case shell	NK-7 high impact polypropylene
Latches	Nylon 66
Handle	NK-7 high impact polypropylene TPE
Purge valve	Nylon 66 Gore® membrane Silicone washers
Pins/hardware	304 stainless steel
Gasket	EPDM

www.pslfireandsafety.co.nz

+64 9 818 8048
 sales@pslfireandsafety.co.nz



NANUK™
 PROFESSIONAL PROTECTIVE CASES

LARGE SERIES **933**

STANDARD FEATURES

- 1 - Powerclaw latching system
- 2 - Waterproof IP67 rated
- 3 - Impact resistant NK-7 resin
- 4 - Padlockable
- 5 - Stackable
- 6 - Molded-in bezel system
- 7 - Soft grip handle stay
- 8 - Automatic pressure release valve
- 9 - Integrated lid stay
- 10 - 100% stainless steel hardware
- 11 - Lifetime guarantee



AVAILABLE COLORS



AVAILABLE OPTIONS



CUSTOM OPTIONS



