



SPECIFICATIONS

Interior dimensions	L22.0 x W17.0" x H12.9" L559mm x W432mm x H328mm
Exterior dimensions	L25.4" x W20.0" x H14.5" L645mm x W508mm x H368mm
Weight (empty)	19.2 lbs 8.7 kg
Lid depth	2.1" 53mm
Base depth	10.8" 274mm
Max buoyancy	167.6 lbs 76 kg
Temperature range	Min -20°F (-29°C) Max 140°F (60°C)
Airline cabin carry-on	No
Watertight	Yes - IP67
Warranty	Conditional lifetime guarantee

CERTIFICATIONS

	IPX7 INGRESS PROTECTION - WATERPROOF
	IP6X INGRESS PROTECTION - DUSTPROOF
	ATA SPECIFICATION 300 - CATEGORY 1 IMPACT
	ASTM D-4169 DC-18 - DROP TEST 48cm (19") min.
	ASTM D-4169 DC-18 - VIBRATION
	ASTM D-4169 DC-18 - RAINFALL
	MIL-STD-810F - IMMERSION 1 meter (3.28 ft)

MATERIALS

Case shell	NK-7 high impact polypropylene
Latches	Nylon 66
Handle	NK-7 high impact polypropylene TPE
Purge valve	Nylon 66 Gore® membrane Silicone washers
Pins/hardware	304 stainless steel
Gasket	EPDM
Backing plate	NK-7 high impact polypropylene
Pull handle	Polycarbonate + ABS Nylon TPE
Wheels	Polyurethane Polycarbonate

www.pslfireandsafety.co.nz

+64 9 818 8048
sales@pslfireandsafety.co.nz



NANUK™
 PROFESSIONAL PROTECTIVE CASES

WHEELED SERIES **960**

STANDARD FEATURES

- 1 - Powerclaw latching system
- 2 - Waterproof IP67 rated
- 3 - Impact resistant NK-7 resin
- 4 - Reinforced metal padlock holes
- 5 - Stackable
- 6 - 2-stage retractable handle
- 7 - Polyurethane wheels
- 8 - Side mounted spring loaded handles
- 9 - Automatic pressure release valve
- 10 - Integrated lid stay
- 11 - Removable lid
- 12 - Top and bottom panel mount
- 13 - 100% stainless steel hardware
- 14 - Lifetime guarantee



AVAILABLE COLORS



AVAILABLE OPTIONS



CUSTOM OPTIONS





www.pslfireandsafety.co.nz

+64 9 818 8048
 sales@pslfireandsafety.co.nz

