

The rugged PSL siren is a single ended siren designed to give effective warning over a wide area. Suitable for disaster, emergency, evacuation etc.



SKU:047900

FEATURES:

- Outer Casting: Light alloy, powder coated with ZINCSHIELD and top coated with Grey DURALLOY XT powder coat
- Impellers: Light alloy, powder coated with ZINCSHIELD and top coated with Red DURALLOY XT powder coat
- Base Plate: Heat treated light alloy, powder coated with ZINCSHIELD and top coated with Grey DURALLOY XT powder coat
- Nuts & Bolts: Stainless steel
- Motorcasing: Aluminium coated with CAPA THANE for weather resistance

SPECIFICATIONS:

Dimensions: Height: 41cm Width: 40cm
Length: 55cm

Weight: 40kg

Range: 4km in still air

Sound Output: 124.5 Decibels at 1 metre
Approximately 525Hz

Power Requirements:

Phase: Single Phase 240V
Starting Amps: 54 amps peak
Running Amps: 10.5 amps
Motor Rated: 14 amps (2.2kW) 3HP
IP55 Weather Rating

Note: There are many factors that will affect the noise level and range of a siren. Background, wind, structures and terrain can all affect the sound pressure wave. These factors must be taken into account when siting and elevating the siren.



www.pslfireandsafety.co.nz

PO Box 69-028 Glendene,
Auckland 0645, NZ
+64 9 818 8048

