

Agent Capacity	9L
Agent Type	Fluorine Free Foam
Gross Weight	12.88kg
Height	586mm
Width	181mm
Discharge Time	45 seconds
Cyl Pressure Test	2.5MPa
Fire Rating	4A: 20B:3F
Approval	AS?NZS 1841.4

PSL Fire & Safety 10 Akatea Road Glendene, Auckland 0602

Phone +64 9 818 8048

sales@pslfireandsafety.co.nz

UFLAME *fighter* III

Flamefighter III Fluorine Free Foam Extinguisher

An exciting new addition to the Fire Extinguisher range is the 9lt Fluorine Free Foam fire extinguisher.

These recently developed fire extinguishers are new to our Flame Fighter III range, they contain specialist "Eco-Friendly" foam in a stainless-steel cylinder, have user friendly, clear instructions, stainless steel handles, large pressure gauge, a specially developed aspirating type applicator nozzle & nickel-plated head assemblies.

These 9lt Fluorine Free Foam fire extinguishers will also fit into the same wall & vehicle brackets used for most previous 9lt foam & water type fire extinguishers.

These fire extinguishers have been tested & approved to AS/NZS Standards & accredited for use on Class A (Combustibles), Class B (Burning Liquids) & unlike most foam fire extinguishers they can also be used Class F fires (Fats & Cooking Oils)