

FIRE HOSE



Inside Diameter	Mass per Metre	Minimum Burst Pressure	Recommended Working Pressure	30m Coil Diameter
38 mm	0.24 kg	5250 kPa	2100 kPa	0.45 m
51 mm	0.33 kg	5250 kPa	2100 kPa	0.48 m
64 mm	0.37 kg	5250 kPa	2100 kPa	0.50 m
65 mm	0.37 kg	5250 kPa	2100 kPa	0.50 m

Features:

- ✓ Spun Percolating fire hose
- ✓ Working Pressure 2100 kPa
- ✓ Type 2
- ✓ Class H
- ✓ Can be stored wet
- ✓ Mildew resistant for long life
- ✓ Shipped complete with fittings if required
- ✓ Australian Standard AS2792
- ✓ 12-months warranty

CENTURION-P® is a premium percolating fire hose designed for professional fire-fighting units manufactured by Crusader Hose. It has been developed by understanding the tough and extreme conditions fire-fighters have to deal with. The extra percolation feature allows seepage of water through the jacket, thus offering protection against burning coals.

This *Class H* hose is woven with spun polyester fibres, which gives excellent abrasion resistance and flexibility. The spun polyester fabric is fully synthetic so it does not require drying after use, although drying does prevent surface mould stains. **CENTURION-P®** has Australian Standard AS 2792 approval. It is used by the NSW Fire Brigade, several brigades of Fire Rescue Victoria, as well as the Australian Army.



www.pslfireandsafety.co.nz

+64 9 818 8048

sales@pslfireandsafety.co.nz

