

PREMIUM FIRE HOSE



Inside Diameter	Mass per Metre	Minimum Burst Pressure	Recommended Working Pressure	30m Coil Diameter
25 mm	0.17 kg	5250 kPa	2100 kPa	0.36 m
38 mm	0.24 kg	5250 kPa	2100 kPa	0.45 m
51 mm	0.33 kg	5250 kPa	2100 kPa	0.48 m
64 mm	0.37 kg	5250 kPa	2100 kPa	0.50 m
65 mm	0.37 kg	5250 kPa	2100 kPa	0.50 m
76 mm	0.46 kg	3500 kPa	1400 kPa	0.57 m
90 mm	0.50 kg	3500 kPa	1400 kPa	0.64 m
102 mm	0.56 kg	2500 kPa	1000 kPa	0.68 m

Features:

- ✓ Excellent abrasion resistance
- ✓ High pressure Class H
- ✓ Lighter than extruded hose
- ✓ Low coil size
- ✓ Mildew resistant
- ✓ Standard approved
- ✓ 12-month warranty

The **CENTURION®** is the fire hose of choice for professional fire-fighting brigades. Crusader Hose has been manufacturing this hose for over 35 years and has continuously improved in performance. It has been developed by understanding the tough and extreme conditions fire-fighters have to deal with.

This *Class H* hose is woven with spun polyester fibres, which gives excellent abrasion resistance and flexibility. This hose is not only lighter and easier to handle compared to an extruded fire hose, it is also easier to roll up and takes up less storage space. Using **CENTURION®**, fire-fighters have less weight to carry when they run up or around a building.

The spun polyester fabric is fully synthetic so it does not require drying after use, although drying does prevent surface mould stains. **CENTURION®** has Australian Standard AS 2792 and Australian Defence Force DEF 5195A approval. It is used by the NSW Fire Brigade, several brigades of Fire Rescue Victoria, as well as the Australian Army.



www.pslfireandsafety.co.nz

+64 9 818 8048

sales@pslfireandsafety.co.nz

