

Jet/Spray

PSL's own manufactured range of Fyrex Nozzles are excellent general purpose/fire fighting nozzles complete with excellent fog spray/jet/shut-off action, variable by rotation of the nozzle tip.

Friction loss 280 kPa measured at a test flow of 4000 l/min.

Precision machined in either gun metal or heat treated aluminium alloy.

FEATURES:

- Fine machining produces excellent fog spray/jet/shut off, variable by rotation of the nozzle tip
- Heavy knurling ensures good secure grip
- Wide bump ring for added tip protection
- Diffuser made from stainless steel for lifetime durability, secured with a self locking nut
- Fine finish internals for maximum flow
- Wide, heavy section, non jam thread for quick action and reliability



SKU:0687-IND



SKU:0689-IND + 118700



SKU:068000

MODELS:

38mm FBSP

- Light Alloy (TA25) (SKU:1257-IND)
- Gun Metal (TB25) (SKU:1264-IND)

45mm FBSP

- Light Alloy (FA25) (SKU:0687-IND)
- Gun Metal (FB25) (SKU:0689-IND)

64mm FBSP

- Light Alloy (FA35) (SKU:068000)
- Gun Metal (FB35) (SKU:128500)

64mm FNH

- Gun Metal (TB35) (SKU:068800)

SPECIFICATIONS:

Inlet:	Flow (@700kPa on Jet):	Throw:	Flow (@700kPa on Spray):	Weight (LA):	Weight (GM)
38mm/45mm	291 lpm	24 m	750 lpm	750 gm	2.25 kg
64mm	1532 lpm	36 m	2741 lpm	4 kg	10 kg

