

FEATURES:

- Rotary Vane Primer
- Controls are easy to operate from one location
- Engine on/off/start rotary switch
- Push button electric start with manual recoil back up
- 12V inlet/outlet socket
- Pressure indication, throttle control and choke control
- Pump pressure gauge and pump compound gauge
- Stainless Steel Frame

Typical performance @ 3 metres suction lift:

Pressure	Output
100 kPa	1600 Litres/min
195 kPa	1500 Litres/min
400 kPa	1175 Litres/min
525 kPa	933 Litres/min
600 kPa	800 Litres/min
700 kPa	750 Litres/min
825 kPa	500 Litres/min
900 kPa	428 Litres/min



SKU: 5005-23-70RV

SPECIFICATIONS:

Pump:

Type: Combination: Pressure/Volume
Intake: 4" (100mm) BSRT
Discharge: 70mm FI Double Lug **Volute**
Body And Head: Marine Grade Aluminium Alloy CC601 Heat-Treated
Impeller: Marine Grade Aluminium Alloy CC601 fully enclosed
Wear Rings: Long wearing PTFE, economical to replace.
Shaft Seal: Spring-loaded mechanical
Priming: Dry sliding vane type with electric clutch. Fast and easy to use. Primes 3m in 10 secs, 7m in 30 secs.

Engine:

Engine Model No: Briggs and Stratton 386447
Type: Vanguard V-Twin air cooled overhead valve with Oil Cooler Heat Exchanger.
Maximum output: 23HP (17.2kW)@ 3600 RPM
 38.26 cu. Displacement: 627CC, 4 cycle
 full pressure lubrication
Fuel Tank: Integral 8.75 LTR
Battery: 12V VRLA Battery
Dry Weight: 87kg (incl battery)
Dimensions: 623mmL x 500mmW x 635mmH
Optional Extras: Round the Pump Proportioner, wheel kit.

