



PHOS-CHEK®
FIRE RETARDANT | FOAM | GEL



SCAN ME

WD881A

CLASS A FOAM CONCENTRATE

PHOS-CHEK® WD881A Class A Foam concentrate is specially formulated to make water more effective for fire fighting. The unique combination of surfactants in WD881A significantly reduces water's surface tension and, when mixed with air, creates a superior foam blanket that surrounds fuels with a thick layer of water. This creates a barrier between the fuel and the fire, knocking down the fire faster than water alone, and allow fire fighters to see the areas of application. Making the water more effective reduces the amount of water needed to extinguish the fire, reduces water damage and increases fire fighter safety through quicker knockdown and reduced mop-up/overhaul requirements.

WD881A is highly effective for fighting Class A fires when mixed with water at use rates of 0.1% to 1.0%. It has proven effectiveness in many applications including Compressed Air Foam Systems (CAFS), structural firefighting, forest fire suppression and prescribed burning, mine fires, industrial Class A fires, and for extinguishing hydrocarbon spill fires. PHOS-CHEK WD881A is the most concentrated Class A foam product



www.pslfireandsafety.co.nz

+64 9 818 8048
sales@pslfireandsafety.co.nz



Quality Management System Certification
ISO 9001:2015



Environmental Management System Certification
ISO 14001:2015



Occupational Health and Safety Management System Certification
ISO 45001:2018

Rev 1: 07/24

WD881A foam concentrate does not contain PFAS chemicals including, but not limited to, PFOS or PFOA. Fluorinated surfactants are used in Class B foam concentrates and are necessary to form a film on flammable liquid fires. Class B foams should not be used on Class A fires. Never mix Class A and Class B foam concentrates.





QUALIFICATIONS AND USES

WD881A is fully tested and qualified for use by the USDA Forest Service under Specification 5100-307b for all application methods including ground engines, Canadair water scooper aircraft, single engine air tankers (SEATS), and fixed tank helicopters. WD881A is compatible with fresh water, sea-water and long-term retardant. Foam characteristics are not affected by freeze-thaw. WD881A contains NO HAZARDOUS INGREDIENTS, is readily biodegradable, and has no flash point, making it safe to use near open flames. WD881A meets the requirements of NFPA 1150 and has superior performance for use in CAF systems.

USE RATES

- Wetting Agent: 0.1%
- Direct Attack: 0.3% to 0.5%
- Mop Up/Overhaul: 0.1% to 0.3%
- Exposure Protection: 1.0%
- Brush (Pre-Treatment): 0.7% to 1.0%

TABLE	RETARDANT	GEL	FOAM	WATER
Indirect Attack	✓✓✓✓	✓✓	✓	
Direct/Parallel Attack	✓✓✓✓	✓✓✓	✓✓	✓
Interior Structure Attack		✓✓	✓✓✓✓	✓
Structure Protection: -Indirect Application	✓✓✓✓	✓✓✓	✓✓	✓
Structure Protection: -Direct Application		✓✓✓✓	✓✓✓	✓
Mop Up	✓✓	✓✓	✓✓✓✓	✓
Prescribed Burn Control	✓✓✓✓	✓✓✓	✓✓	✓

 = Superior Effectiveness
  = Excellent Effectiveness
 = Good Effectiveness
  = Baseline Effectiveness

www.pslfireandsafety.co.nz
 +64 9 818 8048
 sales@pslfireandsafety.co.nz




PRODUCT CHARACTERISTICS

Color/Odor	Tan liquid with a hint of orange blossom
Viscosity	≤50 centipoise (cP) at 70 °F (21 °C)
Weight @70°F (21°C)	8.54 lbs/US gallon (1.024 kg/litre)
pH	6.5 to 8.5, typically 7.5
Surface Tension	26.4 dynes/cm ² @ 0.1%
Flash/Fire Point	Flash and fire point > 212°F when tested by an open cup method
Water Solubility	Readily self-disperses and dissolves in fresh, brackish and sea water at all concentrations
Corrosivity	Meets Interagency Standards (USDA Specification 5100-307b) for aerial and ground application. Approved for use in fixed-tank equipped helicopters

Ordering information	Shipping	Weight	Catalog
WDD881A	lb.*	kg.*	Part #
5 Gallon Pail (19 litres)	45	19	AUPCWD881A20L
55 Gallon Drum (208 litres)	470	212	AUP-CWD881A200L
260 Gallon Tote (985 litres)	2255	1023	10001425

* Approximate shipping weight

*Contact your local authorized PHOS-CHEK distributor or factory sales representative for additional details.

These precautions and practices are similar to those used with any heavy-duty detergent.

Water solutions of WD881 at use levels (0.1%-1.0%) are only minimally irritating, but should be washed from skin as soon as practical, as drying and chapping could result from prolonged exposure.

ENVIRONMENTAL INFORMATION

WD881A Class A foam concentrate does not contain PFAS chemicals commonly found in fluorinated Class B foam concentrates. Perimeter Solutions foam manufacturing process is intentionally separated between fluorinated and non-fluorinated concentrate types, thus eliminating the potential for cross contamination or residual contamination.

HANDLING PRECAUTIONS

For detailed safety information, please refer to the SDS. WD881A concentrate is moderately irritating to eyes and slightly irritating to skin. Prolonged or repeated contact with concentrate may produce skin irritation and inhalation of mists can irritate the nose and upper respiratory system.

- Eye Protection: Goggles are recommended when handling concentrate. If in the eyes, flush immediately with plenty of water for at least 15 seconds.
- Skin Protection: Wear protective clothing and chemical resistant gloves when handling concentrate. Exposed skin should be washed as soon as possible.
- Skin Protection: Wear protective clothing and chemical resistant gloves when handling concentrate. Exposed skin should be washed as soon as possible.
- Respiratory Protection: None required. Avoid breathing mist or vapor.
- Other precautions: Keep container closed. Use with adequate ventilation.

www.pslfireandsafety.co.nz

+64 9 818 8048

sales@pslfireandsafety.co.nz

